Datasheet FWL



INTRODUCTION

The latest generation of directional warning lamp FWL, a Romanian manufacturer MTX, is an ideal solution for additional warning equipment for special and privileged vehicles in road traffic. The lamps are widely applied in police cars, in fire-fighting vehicles, in ambulances, in road service vehicles and in roadside assistance. High quality of materials guarantees excellent resistance to mechanical damage and moisture. Technical parameters, modern design, dedicated optics and a specially designed lampshade give the lamp FWL a significant competitive advantage on the market.



FEATURES

SPECIFICATION

LEDs Warning Patterns Operating Voltage Avg. Current	FWL-Xx*2-y**-ALP CREE 3W LED x 6 pcs. 4 10.9-30VDC A/B*: 0.5A-12V DC/ 0.25A-24V DC R*: 0.4A-12V DC/ 0.2A-24V DC		Cree® LEDs Reverse polarity protection High efficiency and resistant for weather conditions Auto day/night mode	ł	Memorizing the last flash pattern setting 4 Flash Patterns Synchronization up to 10 pcs. Ability to work alternately
Avg. Power	A/B*: 6 W (depends on pattern) R*: 4 W (depends on pattern)				
Max. Current	A/B*: 1A-12V DC / 0.5A-24V DC R*: 0.65A-12V DC / 0.35A-24V DC				
Max. Power	A/B*: 12W R*: 8W				DIMENSIONS
Dimensions	125x28x16,5 mm				
IP Code	IP67			\rightarrow	
Light colour*	B*-Blue, A*-Amber, R*-Red			l)	
Lampshade colour**	B**-Blue, A**-Amber, R**-Red, C**-Colourless				
Operating temperature	-30 °C/ +50 °C				
Synchronization	Max. 10 pcs.				
Fulfils	R65 class 2 , R10				
Wires	Red- VCC-200mm (20AWG) Black- GND-200mm (20AWG) Yellow-Flash Pattern & Sync-200mm (20AWG)				1125
Lifetime***	≥ 35000 h				
 light colour and class lampshade colour estimated lifetime based of APPLICATIONS	n calculated lifetime of critical components			50	

FWL can be widely used in different types of application:

- Car police lights
 - Ambulance lights
- Road service vehicles lights
- Fire-fighting vehicles lights
- Roadside assistance vehicles
- lights

Contact:

+40 748 751 465

sales@mtxledsolutions.com www.mtxledsolutions.com

MTX LED reserves the right to make technical changes without prior notice. Copyright © MTX LED 23.12.2019 V03

Datasheet FWL

MTX LED

MARKS

XA2- Light colour-amber/ Class 2, i.e. day/night mode

- XB2- Light colour-blue/ Class, 2 i.e. day/night mode
- XR2- Light colour-red/ Class, 2 i.e. day/night mode

ACCESORIES

FLASH PATTERNS

	Flash Patterns	
1	Single	
2	Double	
3	Triple	
4	Quad	

	FWL-ACC						
No.	Description	Qty.					
1	Rubber foam pad	1	• •				
3	St. 3,5x20 Screw	2					

ORDERING CODE

Ordering code

190916.063A4023 190916.063A5023 190916.063B3023 190916.063B5023 190916.063C1023 190916.063C5023 190916.00000001 FWL-XA2-A-ALP FWL-XA2-C-ALP FWL-XB2-B-ALP FWL-XB2-C-ALP FWL-XR2-R-ALP FWL-XR2-C-ALP FWL-ACC

Item

Description

Amber light, Amber lampshade, class II Amber light, colourless lampshade, class II Blue light, blue lampshade, class II Blue light, colourless lampshade, class II Red light, red lampshade, class II Red light, colourless lampshade, class II Accessory pack

 Contact:
 40 748 751 465
 sales@mtxledsolutions.com
 www.mtxledsolutions.com

 MTX LED reserves the right to make technical changes without prior notice.
 Copyright © MTX LED 23.12.2019 V03
 V03